

Service levels colour groups:

Back to Basic	2
Lights of Nature	2
Sweet Romance	3
Menpower	3
Mixed Cultures	3
Black & White	3
Fresh & Fruity	3

Technical specifications:

Solar Transmission	7%
Solar Reflection aluminium	60%
Light Transmission	6%
Light Reflection aluminium	59%
UV Transmission	3%
Openness Factor	0,5%
Colour rendering index	98
LT-value *	5%
g-value *	19%
U-value (W/m ² K) *	0,8
Weight (g/m ²)	73
Thickness (mm)	0,21
Width (cm)	220 (+/- 5 cm)
Yarn composition	Polyester

Aluminium adhesion	ISO 2409 class. 0
Corrosion resistance	EN ISO 3231
Formaldehyde free	Yes
PVC free	Yes
Antistatic	Yes
Öko-Tex Standard 100	Yes

Achievable rating according to the European performance rating of shading products, EN 14501:

Glare control	3 (good)
View through	1 (poor)
g-value	3 (good)



Pleated blind



Roller blind



Panel track



*Provides glare control on west to east façades.

* Properties calculated in combination with Solar control glazing (EN 13363-2, ISO 15099). Measurements according to EN 410.

* All advices are based on the usage of clear glass and approximately 50% of the façade consists of glass. There should be no mirroring objects in the vicinity.