

**Service levels colour groups:**

Back to Basic	2
Lights of Nature	2
Sweet Romance	3
Menpower	3
Mixed Cultures	3
Black & White	3
Fresh & Fruity	3

**Technical specifications:**

Solar Transmission	20%
Solar Reflection aluminium	52%
Light Transmission	20%
Light Reflection aluminium	51%
UV Transmission	17%
Openness Factor	14%
Colour rendering index	99
LT-value *	15%
g-value *	22%
U-value (W/m <sup>2</sup> K) *	0,8
Weight (g/m <sup>2</sup> )	73
Thickness (mm)	0,18
Width (cm)	220 (+/- 5 cm)
Yarn composition	Polyester

Aluminium adhesion	ISO 2409 class. 0
Corrosion resistance	EN ISO 3231
Formaldehyde free	Yes
PVC free	Yes
Antistatic	Yes
Öko-Tex Standard 100	Yes


**Achievable rating according to the European performance rating of shading products, EN 14501:**

Glare control	1 (poor)
View through	3 (good)
g-value	2 (mild)

316



Pleated blind



\*Combines very good view through with glare control on northern façades.

\* Properties calculated in combination with Solar control glazing (EN 13363-2, ISO 15099). Measurements according to EN 410.

\* All advices are based on the usage of clear glass and approximately 50% of the façade consists of glass. There should be no mirroring objects in the vicinity.