

### Service levels colour groups:

Back to Basic	1
Lights of Nature	2
Sweet Romance	3
Menpower	3
Mixed Cultures	3
Black & White	3
Fresh & Fruity	3

### Technical specifications:

Solar Transmission	6%
Solar Reflection aluminium	61%
Light Transmission	6%
Light Reflection aluminium	60%
UV Transmission	3%
Openness Factor	0,9%
Colour rendering index	98
LT-value *	4%
g-value *	19%
U-value (W/m <sup>2</sup> K) *	0,8
Weight (g/m <sup>2</sup> )	85
Thickness (mm)	0,18
Width (cm)	220 (+/- 5 cm)
Yarn composition	Trevira CS

\* Properties calculated in combination with Solar control glazing (EN 13363-2, ISO 15099). Measurements according to EN410.

Flame retardant according to:

Aluminium adhesion

Corrosion resistance

Formaldehyde free

PVC free

Antistatic

Öko-Tex Standard 100

DIN 4102 B1

NFPA 701

ISO 6941

BS 5867 Part 2 type B

ISO 2409 class. 0

EN ISO 3231

Yes

Yes

Yes

Yes

### Achievable rating according to the European performance rating of shading products, EN 14501:

Glare control	3 (good)
View through	1 (poor)
g-value	3 (good)

# 809



Intrinsic flame retardant



Pleated blind



Roller blind



Panel track



Vertical blind



\*Provides glare control on west to east façades.

\* All advices are based on the usage of clear glass and approximately 50% of the façade consists of glass. There should be no mirroring objects in the vicinity.