

Service levels colour groups:

Back to Basic	2
Lights of Nature	2
Sweet Romance	3
Menpower	3
Mixed Cultures	3
Black & White	3
Fresh & Fruity	3

Technical specifications:

Solar Transmission	44%
Solar Reflection aluminium	34%
Light Transmission	44%
Light Reflection aluminium	33%
UV Transmission	43%
Openness Factor	40%
Colour rendering index	99
LT-value *	32%
g-value *	27%
U-value (W/m ² K) *	0,9
Weight (g/m ²)	49
Thickness (mm)	0,18
Width (cm)	150 (+/- 5 cm)
Yarn composition	Trevira CS

* Properties calculated in combination with Solar control glazing (EN 13363-2, ISO 15099). Measurements according to EN 410.

Flame retardant according to:

DIN 4102 B1
NF P 92-503 M1
NFPA 701
ISO 6941

Aluminium adhesion
Corrosion resistance metal layer
Formaldehyde free
PVC free
Antistatic
Öko-Tex Standard 100

ISO 2409 class. 0
EN ISO 3231
Yes
Yes
Yes
Yes

Achievable rating according to the European performance rating of shading products, EN 14501:

Glare control 0 (unfit)
View through 3 (good)
g-value 2 (mild)

818



Intrinsic flame retardant



Pleated blind



Curtain



*Very good view through. Insufficient for glare protection. Very suitable in twin product.

* All advices are based on the usage of clear glass and approximately 50% of the façade consists of glass. There should be no mirroring objects in the vicinity.