

858



Intrinsic flame retardant



Pleated blind



Roller blind



Curtain



* Very good view through. Insufficient for glare protection. Very suitable in twin product.

Technical Specifications:

Solar Transmission	56%
Solar Reflection aluminium	30%
Light Transmission	56%
Light Reflection aluminium	29%
UV Transmission	43%
Openness Factor	51%
Colour rendering index	95
LT-value*	40%
g-value*	29%
U-value (W/m ² K)	0,9
Weight (g/m ²)	48
Thickness (mm)	0,18
Width (cm)	220 (+/- 5 cm)
Yarn Composition	Trevira CS
Flame retardant according to	DIN 4102 B1 NF P 92-503 M1 EN 13-773
Aluminium adhesion	ISO 2409 class. 0
Corrosion resistance metal layer	En ISO 3231
Formaldehyde free	Yes
PVC free	Yes
Antistatic	Yes
Öko-Tex Standard 100	Yes
Greenguard (LEED)	Yes
ISO 14001 & ISO 9001	Yes

* All advices are based on the usage of clear glass and approximately 50% of the façade consists of glass. There should be no mirroring objects in the vicinity.

* Properties calculated in combination with Solar control glazing (EN 13363-2), ISO 15099). Measurements according to EN 410.



Verosol