

Service levels colour groups:

Back to Basic	2
Lights of Nature	2
Sweet Romance	3
Menpower	3
Mixed Cultures	3
Black & White	3
Fresh & Fruity	3

Technical specifications:

Solar Transmission	0%
Solar Reflection aluminium	65%
Light Transmission	0%
Light Reflection aluminium	64%
UV Transmission	0%
Openness Factor	0%
Colour rendering index	n/a
LT-value *	0%
g-value *	17%
U-value (W/m ² K) *	0,7
Weight (g/m ²)	270
Thickness (mm)	0,34
Width (cm)	205 (+/- 5 cm)
Yarn composition	Polyester

* Properties calculated in combination with Solar control glazing (EN 13363-2, ISO 15099). Measurements according to EN 410.

Aluminium adhesion	ISO 2409 class. 0
Corrosion resistance	EN ISO 3231
Formaldehyde free	Yes
PVC free	Yes
Antistatic	Yes
Öko-Tex Standard 100	Yes

Achievable rating according to the European performance rating of shading products, EN 14501:

Glare control	4 (very good)
View through	0 (unfit)
g-value	3 (good)

Attention:

For colours in fabric 982, we refer to the non-metallised colours.


982



Pleated blind



Roller blind



*Provides glare control on all façades. Opaque fabrics are perfect in twin products.

* All advices are based on the usage of clear glass and approximately 50% of the façade consists of glass. There should be no mirroring objects in the vicinity.